

ACTIVATION FLEXIBLE HOSE DH11

Description

It is used to connect the various auxiliary bottles to the pilot bottle. Its series connection allows the gas from the master cylinder or pilot bottle to flow through them and actuate the various auxiliary or slave cylinder valves, by pressurising their respective pneumatic actuator heads.



Technical information

ACTIVATION FLEXIBLE HOSE DH 11	
Connections	Bi-chrome tempered steel
Flexible conduct	Synthetic rubber
Connecting thread at both ends	1/4" BSP F revolving
Min. Curvature radius	45 mm
Max. Inclination angle	90°
Length	500 / 600 / 700 / 800 / 1000 / 1250 / 1500 mm
Approvals	UL-EX26559 FM-3055956

WARNING: This type of activation flexible hose DH11, is manufactured and approved to be used with IG-541 Gas. These products are not designed for other use or purpose. If product user has any doubt regarding the application or product use, please contact +34 947 28 11 08. Every not approved use or application or / and any other not approved modification of the product or its function may cause serious accidents or / and personal damages. SIEX 2001 S.L. is not responsible for any non-approved use of the application.

IMPORTANT: SIEX 2001 S.L. reserves the right to change or modify without previous notice any data or specification due to changes or modification in order to improve the products presented.