

## FLEXIBLE HOSE DH-16I

Description

The gas cylinders are connected to the manifold (in the case of manifold cylinders systems) or directly to the pipe of discharge (in the case of modular cylinder) via hoses. This allows for quick and convenient connection of the cylinders on both the time of the assembly and in maintenance or recharging without disassembling the entire network of pipes and bottles.

One end is connected to the outlet of the cylinder valve and the other end to the check valve mounted to the manifold in the manifold cylinders and of modular cylinder discharge pipe connection. Your connection at both ends is performed by rotating nuts that allow quick and efficient threading.

This allows containers off for maintenance or recharge without dismantling other system elements such as joints, pipes, etc...



Technical information

<b>FLEXIBLE HOSE DH 16 I</b>	
Connections	Stainless steel AISI 316
Flexible conduct	Synthetic rubber
Connection thread to the container valve	W21.8x1/14" F revolving
Connection thread to the check valve	1/2" BSP F revolving
Min. Curvature radius	80 mm
Max. Inclination angle	82,5° length 250 mm
Length	250 / 300 / 400 / 500 / 700 / 850 / 1000 / 1250 / 1500 / 2000 mm
<b>Approvals</b>	<b>UL-EX26559</b> <b>FM-3055956</b>

WARNING: This type of flexible hose DH 16 I, is manufactured and approved to be used with IG-541 Gas. These products are not designed for other use or purpose. If product user has any doubt regarding the application or product use, please contact +34 947 28 11 08. Every not approved use or application or / and any other not approved modification of the product or its function may cause serious accidents or / and personal damages. SIEX 2001 S.L. is not responsible for any non-approved use of the application.

IMPORTANT: SIEX 2001 S.L. reserves the right to change or modify without previous notice any data or specification due to changes or modification in order to improve the products presented.